



FEATURES & BENEFITS:

- The removable counterweight makes transporting the DX480LC machine more cost-effective. The removable counterweight can be quickly and easily, lowered or raised. This greatly reduces total operating cost over the life of the machine.
- The new Narrow Adjustable Track Frame makes it possible to transport machine and not have to retract either frame when 30" track shoes are installed. When 36" track shoes are installed only ONE side of the track frame needs to be retracted to meet DOT regulations within most states, further reducing operating cost.
- Overall width on the new DX480LC Fixed Frame is under the 12' DOT regulations, even when 36" track pads are installed. This reduces the transport cost and in turn reduces operating cost.

SPECIFICATIONS:

SPECIFICATION	STANDARD VARIABLE TRACK	NARROW FIXED TRACK	NARROW VARIABLE TRACK
Operating Weight (lb)	108,646	104,310	110,664
Standard Boom Length (ft.in)	23' 4"	23' 4"	23' 4"

SPECIFICATION	STANDARD VARIABLE TRACK	NARROW FIXED TRACK	NARROW VARIABLE TRACK
Standard Arm Length	11' 0"	11' 0"	11' 0"
Max. Reach @ Ground Level	38' 11"	38' 11"	38' 11"
Max. Digging Depth	25' 7"	25' 7"	25' 7"
Drawbar Pull/Tractor Effort (lbf)	74,080	74,080	74,080
Bucket Size (yd ³)	2.49	2.49	2.49
Shoe Size	35"	35"	35"
10' Above Ground Level (lb)	36,030	35,600	36,050
Ground Level (lb)	40,970	40,980	41,020
10' Below Ground Level (lb)	36,970	37,450	37,010
Overall Width-Extended	13' 9"	N/A	12' 5"
Overall Width-Retracted	11' 11"	11' 11"	10' 10"
Track Gauge Extended / Retracted	9' 0" / 10' 10"	9' 0"	9' 6" / 7' 10"
Overall Height	12' 3"	12' 3"	12' 3"
Overall Length	39' 10"	39' 10"	39' 10"